I∩TU**GRID DIU485** ◀

USB-TO-RS485M INTERFACE





CONCEPT

The DIU485 is a USB Interface for Intusonic's RS-485 enabled audio control systems, taking into account the reversed data+ and data- lines of the INTUGRID™ topology. It allows the remote control of INTUGRID™-enabled devices, and likewise enabes the user/installer to configure these devices by e.g. determining source name labels or device names. Catering more for the installer than the end user, the DIU485 is hence an indispensible tool to quickly and swiftly set up an INTUGRID™-enabled system, and to check and confirm whether system communication works. It can likewise be used to trigger events manually for diagnostic purposes and to update firmware over the serial connection. Using the ubiquitious FTDI FT232RL core chip grants universal compatibility with all USB systems, and sporting TVS bus protection gives this unit industrial-grade ruggedness.

G FEATURES

- ▶ USB-to RS485/422 interface with reversed data polarity, 300bps-912.6Kbps
- PC-side connection: USB-A plug, USB 2.0 compliant, USB Powered
 INTUGRID™-side connection: RJ45, max 32 INTUGRID™ devices
- ► Connection to any INTUGRID™-enabled unit via standard Cat5/Cat6 cable
- ► Allows remote control via INTUGRID™ command table
- ▶ Allows remote setting of source name labels and unit names, depending on product
- ▶ Allows remote diagnostics and firmware update over the serial connection
- ► FTDI FT232RL core chip, receive buffer: 256 byte, transmit buffer: 126 byte (FIFO)
- ► ESD protected data lines (15kV)
- ► CE/ROHS compliant



TECHNICAL DATA

Data connectionIntulink™ (RS485) via CAT5/6
Power supplyUSB
PC ConnectionUSB-A
INTUGRID™ connectionRJ45
Number of INTUGRID™ devicesmax. 32
Dimensions WxDxH25x70x20 mm (w/o cable)
Cable length200mm
Weight0.03kg

LOGISTICS DATA

Order Number	2023001
Single unit EAN-13	5060502923530
Single Carton (SC) size WxDxH	221x110x38mm
SC gross weight	0.05 kg
Units per master carton (MC)	n/a
MC size WxDxH	n/a
MC gross weight	n/a

